Application No. 10/580,038 Docket No.: 4436-0127PUS1

Amendment dated February 25, 2009 Response to Office Action of November 4, 2008

Response to Office Action of November 4, 2008

AMENDMENTS TO THE CLAIMS

1 - 2. (Cancelled)

3. (Currently amended) A hearing aid according to claim 9, 1 or 2, where switching

means are provided for switchingthe signal processor further comprising a switch that activates

generation of the the signal processor to a state where the compensation signal is generated when

said auxiliary input is provided.

4. (Currently amended) A hearing aid according to claim 3, where the switching means

are adapted forswitch is automatically generating the compensation signalactivated upon

receiving the auxiliary input.

5. (New) A hearing aid according to claim 9, the hearing aid having at least one

significant opening in the hearing aid or an ear mould or around a tubing leading into the ear

canal.

6. (New) A hearing aid according to claim 9, wherein the wireless receiver is a telecoil

receiver that recieves magnetically transmitted signals, or a radio frequency receiver.

7. (New) A hearing aid according to claim 9, where said signal processor produces said

compensation signal based on the sound signal within the ear canal obtained by the internal input

transducer.

Application No. 10/580,038 Docket No.: 4436-0127PUS1 Amendment dated February 25, 2009

Response to Office Action of November 4, 2008

8. (New) A hearing aid according to claim 9, where said signal processor produces said

compensation signal based on input to said external input transducer.

9. (New) A hearing aid comprising:

an open fitting to reduce occlusion;

a signal path with an external input transducer;

a wireless receiver or a direct audio input receiver providing an auxiliary electric input to

the signal path;

an attenuation portion that attenuates the external input transducer signal or switches it

off;

at least one internal input transducer that obtains a sound signal within the ear canal, said

internal transducer being connected to said signal path;

a signal processor that produces a compensation signal that at least partly attenuates

acoustic signals bypassing the signal path and entering the ear canal; and

an output transducer that produces an output audio signal based on said compensation

signal.